

THIS REPORT HAS BEEN DELIMITED  
AND CLEARED FOR PUBLIC RELEASE  
UNDER DOD DIRECTIVE 5200.20 AND  
NO RESTRICTIONS ARE IMPOSED UPON  
ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;  
DISTRIBUTION UNLIMITED.

# Services Technical Information Agency

limited supply, you are requested to return this copy WHEN IT HAS SERVED  
E so that it may be made available to other requesters. Your cooperation  
ited.

# 40427

IN GOVERNMENT OR OTHER DRAWINGS, SPECIFICATIONS OR OTHER DATA  
ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED  
PROCUREMENT OPERATION, THE U. S. GOVERNMENT THEREBY INCURS  
LIABILITY, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE  
MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE  
S, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY  
OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER  
CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE,  
ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

Reproduced by  
**DOCUMENT SERVICE CENTER**  
KNOTT BUILDING, DAYTON, 2, OHIO

# UNCLASSIFIED

A BIASED ESTIMATE OF THE PROCESS AVERAGE

BY

ALOISE ASKIN AND DONALD GUTHRIE

TECHNICAL REPORT NO. 14

JULY 23, 1954

PREPARED UNDER CONTRACT N6onr 25126  
(NR-042-002)  
FOR  
OFFICE OF NAVAL RESEARCH

GERALD J. LIEBERMAN, DIRECTOR

APPLIED MATHEMATICS AND STATISTICS LABORATORY  
STANFORD UNIVERSITY  
STANFORD, CALIFORNIA

# A BIASED ESTIMATE OF THE PROCESS AVERAGE

By

Aloise Askin and Donald Guthrie

## 1. Summary.

The purpose of this report is to investigate existing estimates of the process average and to propose more sensitive criteria for tightened and reduced<sup>1/</sup> inspection under the double sampling plans of MIL-STD-105A, Sampling Procedures and Tables for Inspection by Attributes.

Under the present MIL-STD-105A procedure for double sampling an estimate of the process average is computed solely on the basis of the first samples from preceding lots. This unbiased estimate is the ratio of the total number of defective items found in the first samples to the total number of items inspected in all of the first samples. If this average falls above the upper limit given for the specified AQL, then tightened inspection is begun. It seems reasonable that "better" criteria can be obtained by using an estimate based on both samples, since the combined sample contains three times the number of items in the first sample.<sup>2/</sup> The term "better" is used in the sense that when quality deteriorates, the probability of going on tightened inspection should be higher than that under the present system.

---

<sup>1/</sup> In its present form, MIL-STD-105A does not provide for reduced inspection under a double sampling plan. However, the present system can be used for finding lower limits for the estimated process average. If the estimate is below this lower limit, reduced inspection can then be instituted. Similarly, criteria for reduced inspection can be obtained by using the procedures presented in this report.

<sup>2/</sup> The results of this paper are based on uncurtailed sampling plans only. That is when the procedure calls for a second sample, the total second sample will be inspected and not just part of it.

A more natural estimate of the process average to use when double sampling is employed is the ratio of the total number of defective items found in both samples from preceding lots to the total number of items inspected. This estimate can be shown to be "biased". That is, if the estimation procedure is repeated over and over again, the average value of the above estimate will be different from the true process average. However, it will be shown that this biased estimate based on the combined samples will be closer, on the average, to the true process average than the unbiased estimate based solely on the first samples.

This report includes a table of the upper limits of the process average for double sampling plans -- Table 1. These limits are based on the biased estimate of the process average described above. Evidence is presented to show that, at least for the range of AQLs included in this report, these limits are "better", in the above sense, than those found in MIL-STD-105A.

Table 2 gives the bias of the above estimate based on both samples, for each AQL and sample size code letter. The bias is defined as the difference between the true process average and the average value of this estimate and is given here for the process average equal to the AQL. It is interesting to note that the bias is always positive. That is, the biased estimate underestimates the true process average, within the range of this table.

In Table 3, a study is made of how "close", on the average, the biased and the unbiased estimates are to the true process average. That is, it compares the respective mean square deviations from the true process average, called the mean square error. It is evident that for each plan

considered, the biased estimate is, on the average, "closer" in the above sense.

2. Procedure For Tightened Inspection When Double Sampling Is Used.

1. After a sufficient number of lots have been inspected according to the procedures in MIL-STD-105A for double sampling, estimate the process average by computing the ratio of the total number of defectives found in all the lots,  $D$ , to the total number of items inspected,  $N$ . Call this estimate  $p_{bk}$ , where  $k$  is the number of lots used to compute  $p_{bk}$ . Convert  $p_{bk}$  to percent by multiplying it by 100.

2. Enter Table 1 with the AQL, sample size code letter,<sup>1/</sup> and the number of lots,  $k$ , used to compute  $p_{bk}$  to find the appropriate upper limit for the process average. Table 1 gives limits for  $k=5, 10$ , and  $15$ .

3. If  $p_{bk}$ , in percent, is above this limit, change to tightened inspection.

For example, consider the following results of inspection using the sampling plan of MIL-STD-105A with code letter F and AQL = 6.5%.

$$n_1 = 10, a_1 = 1, r_1 = 4, n_2 = 20, a_2 = 3, r_2 = 4$$

Lot	Number of defectives		Total defectives both samples	Decision
	1st sample	2nd sample		
1	2	1	3	Accept
2	0	-	0	Accept
3	2	0	2	Accept
4	3	1	4	Reject
5	1	-	1	Accept
6	2	0	2	Accept
7	0	-	0	Accept
8	1	-	1	Accept
9	4	-	4	Reject
10	2	0	2	Accept

<sup>1/</sup> If the sample size code letter is not the same for all samples used, the entry in Table 1 is determined by the code letter of the smallest sample used.

$$D = 19. \quad N = 10(10) + 5(20) = 200.$$

$$p_{b,10} = \frac{D}{N} = .095 \quad \text{or } 9.5\%.$$

Upper limit from Table 1 for  $k=10$  is 10.604%.

Since  $p_{bk}$  is less than the upper limit, normal inspection should be continued.

3. Notation Used in This Report.

$p$	true fraction defective <sup>1/</sup>
$q = 1-p$	true fraction non-defective
$p_1$	unbiased <sup>2/</sup> estimate of $p$ based on the first sample from one lot
$p_b$	biased estimate of $p$ based on both samples from one lot
$p_{bk}$	biased estimate of $p$ based on both samples from each of $k$ lots
$p_u$	unbiased estimate of $p$ based on both samples from one lot
$a_1$	acceptance number for first sample
$a_2$	acceptance number for second sample
$r_1$	rejection number for first sample
$r_2$	rejection number for second sample
$d_1$	number of defectives in first sample
$d$	total number of defectives in both samples from one lot
$D$	total number of defectives in both samples from each of $k$ lots
$n_1$	size of first sample
$n_2$	size of second sample
$n$	total number of items inspected in one lot

<sup>1/</sup> This parameter is often called  $p'$  in Quality Control work. It should be emphasized that  $p_1$ ,  $p_b$ , and  $p_u$  are not parameters but statistics which estimate  $p$ .

<sup>2/</sup> An unbiased estimate is one such that, if the estimation procedure is repeated over and over again, the average value of the estimate will be equal to the true fraction defective.

N            total number of items inspected in k lots  
 AQL          acceptable quality level, as defined in MIL-STD-105A.

4. Estimates of the Fraction Defective.

Consider three estimates of the fraction defective  $p$  based on an uncurtailed double sampling plan for inspection by attributes:

$$1. \quad p_1 = \frac{d_1}{n_1}$$

$$2. \quad p_u = \frac{d_1}{n_1} \quad \text{when a decision is made on one sample only, } r_1 \leq d_1 \leq a_1$$

$$p_u = \frac{\sum_{y_0=a_1+1}^{r_1-1} \binom{n_1-1}{y_0-1} \binom{n_2}{d-y_0}}{\sum_{y_0=a_1+1}^{r_1-1} \binom{n_1}{y_0} \binom{n_2}{d-y_0}} \quad \text{when two samples are taken, where}$$

$$\binom{m}{s} = \frac{m!}{s!(m-s)!}, \quad a_1 < d < n_2 + n_1.$$

$$3. \quad p_b = \frac{d}{n} \quad \begin{array}{ll} d = 0, 1, \dots, a, r_1, \dots, n_1 & \text{when } n = n_1 \\ d = a+1, \dots, n_2 + r_1 - 1 & \text{when } n = n_1 + n_2 \end{array}$$

$$p_{bk} = \frac{D}{N} = \frac{\sum_{i=1}^k d_i}{\sum_{i=1}^k n_i}.$$

The estimate  $p_1$  is an unbiased one based on the first sample only. It is the one on which the estimate in MIL-STD-105A is based.  $p_u$  is also unbiased, but it takes into account the additional information provided by the second sample. Since the computation involved in finding  $p_u$  is relatively difficult, it is rarely used in practical applications. The tables in this report are based on the third estimate,  $p_b$  or  $p_{bk}$ . It is a biased estimate



based on both samples. In the case where a decision can be made from the first sample only,  $p_b = p_u = p_l$ .

It will be shown in Section 6 that, for sufficiently small values of the fraction defective,  $p$ , the mean square error of  $p_b$  is less than or equal to that of either  $p_l$  or  $p_u$ .<sup>1/</sup> From this it follows directly that the variance of  $p_b$  is less than or equal to that of either of the other estimates.<sup>2/</sup> Thus, within this range of  $p$ ,  $p_b$ , although biased, is a better estimate of  $p$  than are  $p_l$  and  $p_u$ , because any limits based on its variance will be narrower, and therefore more sensitive for detecting a process average significantly different from the AQL. In addition, having a smaller mean square error,  $p_b$  will be closer on the average to the true fraction defective  $p$  than  $p_l$  or  $p_u$ .

##### 5. Preparation and Use of the Tables.

Table 1 gives three sets of upper limits for the process average. The first set applies if the process average is estimated on the basis of five lots, the second for ten lots, and the third for fifteen lots. Limits are given for each AQL and each sample size code letter.

The upper limit is a "three-sigma" limit, and is given by the expression  $E(p_{bk}) + 3\sigma_{p_{bk}}$  where  $E(p_{bk})$  is the expected (average) value of  $p_{bk}$  and  $\sigma_{p_{bk}}$  is the standard deviation<sup>3/</sup> of the estimate. Both  $E(p_{bk})$  and  $\sigma_{p_{bk}}$  are computed for  $p$  equal to the AQL.

$$1/ E(p_b - p)^2 \leq E(p_l - p)^2 \text{ and } E(p_b - p)^2 \leq E(p_u - p)^2 \text{ for some range of small } p.$$

$$2/ E[p_b - E(p_b)]^2 \leq E[p_l - p]^2 \text{ and } E[p_b - E(p_b)]^2 \leq E[p_u - p]^2 \text{ for some range of small } p.$$

$$3/ \sigma_{p_{bk}} = \sqrt{E[p_{bk} - E(p_{bk})]^2} = \frac{\sigma_{p_{b1}}}{\sqrt{k}}.$$

The limits are such that, if the process average is at the AQL, the probability of an estimate  $p_{bk}$  falling above its limit is small (about .00135). In this respect, they resemble those of MIL-STD-105A. However, since the standard deviation and the mean square error of  $p_{bk}$  are less than those of the old estimate  $p_1$ ,<sup>1/</sup> (at least for AQL's within the range of the tables), these limits are stricter, and the probability of detecting a deviation of  $p$  from the AQL is therefore greater than it is when  $p_1$  is used.

Table 2 gives, for each AQL and sample size code letter, the bias of the estimate  $p_b$ , i.e., the difference between the true fraction defective  $p$  and the expected value of  $p_b$ . This is independent of  $k$  and is expressed in the form  $E(p-p_b)$  or  $p-E(p_b)$ .

Using Table 3, one can compare the mean square errors of the two estimates  $p_b$  and  $p_1$ . These are expressed by  $E(p_b-p)^2$  and  $E(p_1-p)^2$ . It is seen that in every sampling plan considered in this report,  $p_b$  has the lower mean square error.

#### 6. Comparison of the Mean Square Errors of $p_b$ and $p_1$ .

It now remains to prove the following theorem:

$$(6.1) \quad E(p_b-p)^2 \leq E(p_1-p)^2 \quad \text{for some range of small } p,$$

where  $E(p_b-p)^2 = E(\frac{d}{n}-p)^2$  is the mean square error of  $p_b = \frac{d}{n}$ , the biased estimate of  $p$  based on two samples, and  $E(p_1-p)^2 = \frac{pq}{n_1}$  is the mean square error (or variance) of  $p_1 = \frac{d_1}{n_1}$ , the unbiased estimate based on the first sample.

Theorem.  $E(\frac{d}{n}-p)^2 \leq \frac{pq}{n_1}$  for some range of small  $p$ .

---

<sup>1/</sup> See Table 3.

Proof. Case I:  $a_1 > 0$

$$\begin{aligned} E\left(\frac{d}{n} - p\right)^2 &= \frac{pq}{n_1} - \left\{ \frac{1}{n_1^2} - \frac{1}{(n_1+n_2)^2} \right\} \sum_{d=a_1+1}^{n_1-1} (d-n_1p)^2 \binom{n_1}{d} p^d q^{n_1-d} \\ &\quad + \frac{n_2 pq}{(n_1+n_2)^2} \sum_{d=a_1+1}^{n_1-1} \binom{n_1}{d} p^d q^{n_1-d} . \end{aligned}$$

We wish to discover under what condition on  $p$  is

$$\left\{ \frac{1}{n_1^2} - \frac{1}{(n_1+n_2)^2} \right\} \sum_{d=a_1+1}^{r_1-1} (d-n_1p)^2 \binom{n_1}{d} p^d q^{n_1-d} \geq \frac{n_2 pq}{(n_1+n_2)^2} \sum_{d=a_1+1}^{r_1-1} \binom{n_1}{d} p^d q^{n_1-d}$$

or

$$(6.2) \quad \frac{n_2+2n_1}{n_1^2} \sum_{d=a_1+1}^{r_1-1} (d-n_1p)^2 \binom{n_1}{d} p^d q^{n_1-d} \geq pq \sum_{d=a_1+1}^{r_1-1} \binom{n_1}{d} p^d q^{n_1-d} .$$

This inequality is always satisfied if  $(d-n_1p)^2 \geq 1$  and if  $\frac{n_2+2n_1}{n_1^2} \geq pq$ .

Now,  $(d-n_1p)^2 \geq 1$  implies that  $-1 \geq d-n_1p \geq 1$  or  $\frac{d+1}{n_1} \leq p \leq \frac{d-1}{n_1}$ ,  $d = a_1+1, \dots, r_1-1$ . Hence, upon inserting the largest value for  $d$  on the left side of this inequality, and the smallest value for  $d$  on the right side, we obtain the condition

$$(6.31) \quad \frac{r_1}{n_1} \leq p \leq \frac{a_1}{n_1} .$$

The condition  $pq \leq \frac{n_2+2n_1}{n_1^2}$  reduces to the quadratic inequality in  $p$ ,

$$p^2 - p + \frac{n_2+2n_1}{n_1^2} \geq 0 \quad 0 \leq p \leq 1 .$$

Upon setting the left side of this inequality equal to zero, and solving for  $p$ , we find that the inequality is satisfied if either

$$(6.32) \quad p \leq \frac{n_1 - \sqrt{n_1^2 - 4n_2 - 8n_1}}{2n_1} \quad \text{or} \quad p \geq \frac{n_1 + \sqrt{n_1^2 - 4n_2 - 8n_1}}{2n_1}$$

and it is true for all  $p$  between zero and one if  $n_1^2 - 4n_2 - 8n_1 \leq 0$ , that is, if  $n_2 \geq \frac{n_1(n_1 - 8)}{4}$ . Inequalities (6.31) and (6.32) are conditions on  $p$  which, if they are satisfied, are sufficient to guarantee that  $E(\frac{d}{n} - p)^2 \leq \frac{E_1}{n_1}$ .

A somewhat different condition on  $p$  can be found by substituting  $\sum_{d=a_1+1}^{r_1-1} (d - n_1 p)^2 \binom{n_1}{d} p^d q^{n_1-d}$  in (6.2),

$$\begin{aligned} & (a_1^2 - 2a_1 n_1 p) \sum_{j=1}^b \binom{n_1}{a_1+j} p^{a_1+j} q^{n_1-a_1-j} + 2a_1 \sum_{j=1}^b j \binom{n_1}{a_1+j} p^{a_1+j} q^{n_1-a_1-j} \\ & + \sum_{j=1}^b (j - n_1 p)^2 \binom{n_1}{a_1+j} p^{a_1+j} q^{n_1-a_1-j}, \end{aligned}$$

where  $b = r_1 - 1 - a_1$ . Inequality (6.2) becomes

$$\begin{aligned} (6.4) \quad & \left( \frac{n_2 + 2n_1}{n_1^2} \right) \left\{ (a_1^2 - 2a_1 n_1 p - \frac{n_1^2 p q}{n_2 + 2n_1}) \sum_{j=1}^b \binom{n_1}{a_1+j} p^{a_1+j} q^{n_1-a_1-j} \right. \\ & \left. + 2a_1 \sum_{j=1}^b j \binom{n_1}{a_1+j} p^{a_1+j} q^{n_1-a_1-j} + \sum_{j=1}^b (j - n_1 p)^2 \binom{n_1}{a_1+j} p^{a_1+j} q^{n_1-a_1-j} \right\} \\ & \geq 0. \end{aligned}$$

Since the second and third terms are positive for all  $p$ , this inequality always holds if

$$a_1^2 - 2a_1 n_1 p - \frac{n_1^2 p q}{n_2 + 2n_1} \geq 0$$

or

$$n_1^2 p^2 - p \left\{ n_1^2 + 2a_1 n_1 (n_2 + 2n_1) \right\} + a_1^2 (n_2 + 2n_1) \geq 0.$$

By setting the left hand side equal to zero, and solving for p, we find that (6.4) is always satisfied if

$$(6.41) \quad p \leq \frac{n_1 + 2a_1(n_2 + 2n_1)}{2n_1} - \frac{\sqrt{n_1^2(4a_1 + 1)^2 + 4a_1n_1(n_2 + 4a_1n_2 - 2a_1) + 4a_1^2n_2(n_2 - 1)}}{2n_1}.$$

The relationships (6.32) and (6.41) will never yield negative values for p since the inequalities  $p^2 - p + \frac{n_2 + 2n_1}{n_1^2} \geq 0$  and  $n_1^2 p^2 - p \left\{ n_1^2 + 2a_1n_1(n_2 + 2n_1) \right\} + a_1^2(n_2 + 2n_1) \geq 0$  are both satisfied for p = 0.

Hence, for some interval about p = 0,  $E(\frac{d}{n} - p)^2 \leq \frac{pq}{n_1}$ .

Case II:  $a_1 = 0$ .

As in Case I, the inequality

$$\begin{aligned} \varphi(p) = & \left\{ a_1^2 - 2a_1n_1p - \frac{n_1^2(p-p^2)}{n_2 + 2n_1} \right\} \sum_{j=1}^b \binom{n_1}{a_1+j}_p a_1^j q^{n_1-a_1-j} \\ & + 2a_1 \sum_{j=1}^b j \binom{n_1}{a_1+j}_p a_1^j q^{n_1-a_1-j} + \sum_{j=1}^b (j-n_1p)^2 \binom{n_1}{a_1+j}_p a_1^j q^{n_1-a_1-j} \geq 0 \end{aligned}$$

must be satisfied. When  $a_1 = 0$ , this becomes

$$\varphi(p|a_1=0) = - \frac{n_1^2(p-p^2)}{n_2 + 2n_1} \sum_{j=1}^{r_1-1} \binom{n_1}{j}_p j q^{n_1-j} + \sum_{j=1}^{r_1-1} (j-n_1p)^2 \binom{n_1}{j}_p j q^{n_1-j} \geq 0.$$

The function  $\varphi(p|a_1=0)$  is a continuous function. Taking the derivative of  $\varphi(p|a_1=0)$  with respect to p, we find

$$\begin{aligned}\varphi'(p|a_1=0) = & -\frac{n_1^2+pq}{n_2+2n_1} \sum_{j=1}^{r_1-1} \binom{n_1}{j} \frac{(j-pn_1)}{pq} p^j q^{n_1-j} \\ & + \left(-\frac{n_1^2}{n_2+2n_1} + \frac{2n_1^2 p}{n_2+2n_1}\right) \sum_{j=1}^{r_1-1} \binom{n_1}{j} p^j q^{n_1-j} + \sum_{j=1}^{r_1-1} (j-n_1 p)^2 \binom{n_1}{j} \frac{(j-n_1 p)}{pq} p^j q^{n_1-j} \\ & + \sum_{j=1}^{r_1-1} (-2n_1)(j-n_1 p) \binom{n_1}{j} p^j q^{n_1-j},\end{aligned}$$

and, setting  $p=0$ ,  $\varphi'(0|a_1=0) = \binom{n_1}{1} = n_1 > 0$ .

Therefore, since  $\varphi(p|a_1=0)$  is an increasing function of  $p$  in at least a small interval about  $p=0$ , and since  $\varphi(0|a_1=0)=0$ , the function must be positive for all  $p$  in some interval about  $p=0$ . For these values of  $p$ ,  $E(\frac{d}{n} - p)^2 \leq \frac{pq}{n_1}$ .

A similar proof can be given for the theorem that  $E(p_b - p)^2 \leq E(p_u - p)^2$  for some range of small  $p$ .

Table 1. Upper limits for the process average for double sampling when the process average is based upon the results of both samples in the preceding 5, 10, or 15 lots. When 5 lots have been used, read the black figures, for 10 lots read the red figures, and for 15 lots read the green figures.

Sample Size Code Letter	Acceptable Quality Level													
	.015	.035	.065	.10	.15	.25	.40	.65	1.0	1.5	2.5	4.0	6.5	10.0
D														23.389
														19.041
														17.114
E													12.865	18.553
													10.266	15.427
													9.114	14.042
F												7.992	12.851	19.268
												6.336	10.604	16.252
												5.602	9.608	14.916
G											5.037	8.197	10.939	18.129
											3.980	6.732	9.199	15.549
											3.512	6.083	8.428	14.407
H										4.023	5.071	7.867	11.395	16.861
										3.223	4.167	6.609	9.804	14.751
										2.869	3.767	6.051	9.099	13.816
I									2.034	3.581	4.361	6.612	9.747	15.444
									1.602	2.904	3.644	5.666	8.553	13.726
									1.410	2.605	3.327	5.247	8.024	12.965
J								1.322	2.219	2.708	4.335	6.334	9.749	14.472
								1.038	1.806	2.252	3.692	5.518	8.670	13.077
								0.913	1.623	2.050	3.407	5.157	8.192	12.459
K						0.814	1.594	1.808	2.728	4.489	6.255	9.186	14.005	
						0.637	1.289	1.503	2.309	3.870	5.521	8.285	12.772	
						0.559	1.154	1.368	2.124	3.596	5.196	7.886	12.225	
L						0.509	0.982	1.245	1.936	2.723	4.234	6.151	9.143	13.155
						0.396	0.791	1.028	1.627	2.329	3.695	5.478	8.305	12.143
							0.346	0.707	0.932	1.490	2.155	3.456	5.179	7.934
M					0.306	0.673	0.988	1.266	1.815	2.654	3.949	5.953	8.825	12.772
					0.238	0.539	0.808	1.063	1.552	2.302	3.502	5.365	8.109	11.910
					0.207	0.480	0.729	0.973	1.436	2.146	3.304	5.104	7.792	11.528
N				0.205	0.442	0.540	0.857	1.260	1.744	2.483	3.786	5.489	8.374	12.408
				0.159	0.351	0.441	0.712	1.069	1.509	2.181	3.392	5.017	7.779	11.660
				0.138	0.311	0.396	0.648	0.984	1.405	2.047	3.218	4.809	7.516	11.328
O			0.134	0.295	0.342	0.553	0.803	1.146	1.656	2.491	3.521	5.314	8.065	11.915
			0.103	0.234	0.277	0.457	0.679	0.990	1.454	2.046	3.205	4.910	7.573	11.313
			0.090	0.207	0.249	0.415	0.623	0.921	1.365	1.938	3.065	4.731	7.355	11.046
P		0.073	0.176	0.216	0.331	0.493	0.742	1.041	1.516	2.114	3.276	4.981	7.817	11.568
		0.056	0.141	0.176	0.274	0.417	0.639	0.919	1.358	1.924	3.033	4.675	7.416	11.086
		0.049	0.125	0.159	0.249	0.384	0.593	0.864	1.288	1.839	2.926	4.539	7.239	10.872
Q	0.032	0.092	0.124	0.192	0.296	0.424	0.616	0.944	1.350	1.951	3.081	4.697	7.413	11.152
	0.024	0.073	0.103	0.162	0.252	0.370	0.548	0.854	1.241	1.813	2.903	4.480	7.133	10.803
	0.021	0.065	0.093	0.148	0.232	0.346	0.518	0.814	1.192	1.752	2.825	4.383	7.009	10.649

Note: all figures in the table are read in percent.

Table 2

1/ The Bias of the Biased Estimate of the Process Average Based on Both Samples of a Double Sampling Plan

Sample Size Code Letter	Acceptable Quality Level													
	.015	.035	.065	.10	.15	.25	.40	.65	1.0	1.5	2.5	4.0	6.5	10.0
D														1.458
E													2.511	2.118
F												1.662	1.322	1.028
G										1.072	0.805	1.502	0.678	
H									0.207	0.514	0.430	0.537	0.344	
I								0.442	0.228	0.585	0.618	0.829	0.422	
J							0.297	0.192	0.350	0.362	0.451	0.436	0.292	
K						0.189	0.097	0.232	0.200	0.124	0.251	0.390	0.206	
L					0.126	0.069	0.145	0.118	0.121	0.106	0.148	0.218	0.299	
M				0.078	0.035	0.025	0.076	0.082	0.049	0.077	0.056	0.119	0.172	
N			0.054	0.019	0.050	0.038	0.042	0.059	0.049	0.058	0.121	0.157	0.147	
O			0.035	0.013	0.029	0.022	0.023	0.037	0.033	0.045	0.059	0.064	0.116	0.141
P		0.019	0.010	0.020	0.013	0.015	0.010	0.027	0.024	0.036	0.052	0.064	0.052	0.078
Q	0.009	0.006	0.015	0.012	0.005	0.011	0.016	0.014	0.023	0.020	0.026	0.045	0.044	0.039

1/ The bias is computed for the process average equal to the AQL and is given by  $AQL - E(p_{bk})$  where  $p_{bk}$  is the biased estimate being considered, and  $E(p_{bk})$  is the average value of  $p_{bk}$ .

Note: All values in the table are read in percent.



Table 3. Comparison of the "Mean Square Errors from the True Process Average"<sup>1/</sup> between 1) the unbiased estimate of the true process average based on the first sample and 2) the biased estimate of the true process average based on both samples for double sampling plans. The top figure in each cell refers to the unbiased estimate, while the bottom figure refers to the biased estimate.

Sample Size Code Letter	Acceptable Quality Level													
	.015	.035	.055	.10	.15	.25	.40	.65	1.0	1.5	2.5	4.0	6.5	10.0
D														180.0
E													86.8	124.6
F												38.4	50.1	67.7
G											16.2	20.5	34.5	90.0
H											8.4	25.6	40.5	59.9
I												14.6	21.9	60.0
J										5.9	9.8	15.4	24.3	43.5
K										4.2	5.6	10.4	16.7	36.0
L									2.8	4.2	7.0	11.0	17.4	29.0
M									1.4	3.0	3.7	6.2	9.9	25.7
N									1.3	3.0	4.9	7.7	12.2	18.0
O									0.6	1.1	2.8	4.5	7.7	12.7
P									0.9	1.3	2.0	5.1	8.1	12.0
Q									0.5	0.7	1.2	3.6	5.4	9.9
						0.2	0.4	0.6	1.0	1.5	2.4	3.8	6.1	9.0
						0.1	0.2	0.3	0.6	1.0	1.9	3.0	4.6	6.7
						0.100	0.166	0.266	0.431	0.660	0.985	1.625	2.560	4.052
						0.037	0.118	0.209	0.272	0.453	0.807	1.301	2.245	3.333
						0.050	0.075	0.125	0.199	0.323	0.495	0.739	1.219	3.039
						0.017	0.054	0.067	0.138	0.238	0.362	0.594	1.007	4.500
						0.022	0.033	0.050	0.083	0.133	0.215	0.330	0.492	3.642
						0.007	0.024	0.028	0.059	0.101	0.159	0.265	0.391	3.000
						0.007	0.013	0.030	0.050	0.080	0.129	0.198	0.296	2.369
						0.002	0.008	0.011	0.037	0.069	0.098	0.163	0.236	1.800
						0.001	0.003	0.006	0.010	0.015	0.025	0.040	0.078	1.510
						0.000	0.002	0.003	0.006	0.013	0.019	0.030	0.051	0.900
														0.790

<sup>1/</sup>The mean square errors are computed for the process average equal to the AQL. If the unbiased estimate is denoted by  $p_1$  and the biased estimate by  $p_b$ , the top figure in each cell is  $E(p_1 - AQL)^2$  and the bottom figure is  $E(p_b - AQL)^2$ , i.e., the average value of  $(p_1 - AQL)^2$  and the average value of  $(p_b - AQL)^2$  respectively.

Note: The figures for the "mean square errors" are based upon the estimates of the percent defective (rather than fraction defective).

STANFORD UNIVERSITY  
Technical Reports      Distribution List  
Contract N6onr 25126

ASTIA, Western Regional Office 5504 Hollywood Blvd. Los Angeles 28, California	1	Planning Research Division Deputy Chief of Staff Comptroller, U. S. Air Force The Pentagon Washington 25, D. C.	1
Armed Services Technical Infor- mation Agency Documents Service Center Knott Building Dayton 2, Ohio	5	Chief of Naval Research Office of Naval Research Washington 25, D. C. Attn: Code 433 (Statistics Branch)	2
Asst. Chief of Staff, G-4 United States Army Procurement Division Standards Branch Washington 25, D. C.	15	Chief of Ordnance United States Army Research and Development Division Washington 25, D. C. Attn: Brig. General L. E. Simon Mr. Charles Bicking	1 1
Chief, Bureau of Aeronautics Department of the Navy Washington 25, D. C.	1	Commander U. S. Naval Ordnance Test Station Inyokern, China Lake, Calif.	1
Chief, Bureau of Ordnance QCC Department of the Navy Quality Control Division Washington 25, D. C.	1	Commanding General Army Chemical Center Quality Assurance Branch Edgewood, Maryland	2
Chief, Bureau of Ordnance QCD Department of the Navy Quality Control Division Washington 25, D. C.	1	Commanding Officer Ballistics Research Lab. U. S. Proving Grounds Aberdeen, Maryland Attn: Mr. R. H. Kent	2
Chief, Bureau of Ordnance QC5 Department of the Navy Quality Control Division Washington 25, D. C.	2	Commanding Officer Office of Naval Research Branch Office 1000 Geary Street San Francisco 9, California Attn: Dr. J. D. Wilkes	1 1
Chief, Bureau of Ships Asst. Chief for Research and Development Department of the Navy Washington 25, D. C.	2	Commanding Officer Office of Naval Research Branch Office Navy No. 100 Fleet Post Office New York, N. Y.	2
Chief, Statistical Engineering Laboratory National Bureau of Standards Washington 25, D. C.	1	Director of Research Operations Research Office U. S. Army Fort McNair Washington 25, D. C.	1
Chief of Naval Research Office of Naval Research Washington 25, D. C. Attn: Code 432 (Mathematics Branch)	1		

Inspection Division Army Quartermaster Corps 111 East 16th St. New York, N. Y. Attn: Mr. David Schwartz	1	Commanding General Air Materiel Command Quality Control Division MCPLXP Wright-Patterson Air Force Base Dayton, Ohio	15
Director, Naval Research Lab. Washington 25, D. C. Attn: Technical Information Officer	6	Director of Research & Development AFDRD-RE-3 Washington 25, D. C.	1
Commanding Officer Signal Corps Supply Agency 225 South 18th St. Philadelphia 3, Pa. Attn: Chief, Quality Control Branch, SIGSU-H6d Inspection Engineering Division	2	Chief, Statistical Engineering Laboratory National Bureau of Standards Washington 25, D. C.	1
Commanding General New York Quartermaster Procurement Agency Inspection Division 111 East 16th St. New York, N. Y.	2	Chief of Naval Materiel Code M553 Department of the Navy Washington 25, D. C.	1
Dr. Clifford J. Maloney Chief, Statistics Branch Chemical Corps Biological Labs. Physical Sciences Division Camp Detrick, Maryland	1	Director Office of Naval Research Branch Office 844 North Rush St. Chicago 11, Illinois	1
Commanding Officer 9926 Technical Service Unit Armed Services Medical Procurement Agency Inspection Division 84 Sands Street Brooklyn, N. Y.	1	Director Office of Naval Research Branch Office 1030 E. Green St. Pasadena 1, California	1
Chief, Inspection Division Office of Standardization Defense Supply Management Agency The Pentagon Washington 25, D. C.	2	Chairman Research & Development Board The Pentagon Washington 25, D. C.	2
Commanding Officer Central Air Procurement District West Warren Ave. and Lonyo Blvd. Detroit 32, Michigan Attn: Director, Quality Control	1	Assistant Chief of Staff, G-4 for Research & Development U. S. Army Washington 25, D. C.	1
		Chief of Naval Operation Operations Evaluation Group-OP342E The Pentagon Washington 25, D. C.	1

Commanding General Air Proving Ground Eglin Air Force Base Eglin, Florida	1	Frankford Arsenal Artillery Ammunition Dept. Inspection Engineering Division Philadelphia 37, Pa.	1
Commander U. S. Naval Proving Ground Dahlgren, Virginia	1	U. S. Naval Ordnance Plant Department of the Navy Indianapolis 18, Indiana	1
Office of Naval Research Logistics Branch Code 436 T-3 Building Washington, D. C.	1	Dr. Paul R. Rider Chief, Mathematical Statistics Group Flight Research Laboratory Wright Air Development Center Wright-Patterson Air Force Base Dayton, Ohio	1
Logistics Research Project George Washington University 707 22nd Street, N.W. Washington 7, D. C.	1	Mr. T. M. Vining Chief, Test Projects Branch Products Division Chemical Corps Engineering Agency Army Chemical Center Maryland	1
Asst. for Operations Analysis Headquarters, U. S. Air Force Washington 25, D. C.	1	Commanding General Ordnance Ammunition Center Joliet, Illinois Attn: ORDLY-I-V	3
Ames Aeronautical Laboratory Moffett Field, California Attn: Technical Librarian	1	Chief, Procurement Maintenance Engineering Division Fort Monmouth, New Jersey Attn: Procurement Data Branch SIGEL-PMP-1	1
N.A.C.A. 1724 F Street, N.W. Washington 25, D. C. Attn: Chief, Office of Aeronautical Intelligence	1	Northeastern Air Procurement District Attn: NEQC 14 Court Square Boston 8, Massachusetts	1
Los Angeles Engineering Field Office Air Research and Development Command 5504 Hollywood Blvd. Los Angeles 28, California Attn: Mr. Chester Pierce	1	Central Air Procurement District Attn: CEQC W. Warren Ave. & Lonyo Blvd. Detroit 32, Michigan	1
U. S. Air Force Engineering Liaison Office Ames Aeronautical Laboratory Moffett Field, California Attn: Mr. Carl Tusch	1	Western Air Procurement District Attn: WEQC 155 W. Washington Blvd. P. O. Box 3849, Terminal Annex Los Angeles 54, California	1
Frankford Arsenal VT Fuze Department Inspection Division Philadelphia 37, Pa. Attn: ORDBA-VK	2	Midcentral Air Procurement District Attn: MIQC 165 North Canal Street Chicago 6, Illinois	1

Southern Air Procurement District  
Attn: SOQC  
3309 Winthrop  
P. O. Box 9038  
Fort Worth 7, Texas 1

Eastern Air Procurement District  
Attn: EAQC  
655 Madison Avenue  
New York 21, N. Y. 1

U. S. Naval Ordnance Test Station  
125 South Grand Ave.  
Mail Station 54  
Pasadena, California 1

Commanding General  
Marine Corps Depot of Supplies  
1100 South Broad Street  
Philadelphia 46, Pa. 1

Naval Inspector of Ordnance  
50 W. Main Street  
Rochester 4, N. Y.  
Attn: Mr. Wollman 1

Chief, Thermionics Branch  
Evans Signal Laboratory  
Belmar, New Jersey  
Attn: Mr. Ross Kilgore 1

Test and Evaluation Laboratory  
U. S. N. Underwater Ordnance  
Station  
Newport, Rhode Island 1

Q. E. Laboratory  
U. S. Naval Ammunition Depot  
Crane, Indiana 1

Commanding Officer  
Rock Island Arsenal  
Rock Island, Illinois  
Attn: Engineering Officer 1

Scranton Ordnance Plant  
156 Cedar Avenue  
Scranton, Pa.  
Attn: Mr. Carl D. Larson  
Chief Inspector 1

Office of Technical Services  
Department of Commerce  
Washington 25, D. C. 1

Captain Burdette T. Person  
Chief, Quality Control Branch  
Central Air Procurement District  
1279 W. Third St.  
Cleveland 13, Ohio 2

Air Force Plant Representative Office  
Central Air Procurement District  
General Electric Company  
Lockland 15, Ohio 1

RAND Corporation  
1500 Fourth St.  
Santa Monica, California 1

Statistical Laboratory  
Department of Mathematics  
University of California  
Berkeley 4, California 1

Kimberly Corporation  
8476 Warner Drive  
Culver City, California  
Attn: Miss Lucille M. Leis  
Office Manager 1

Dr. Adam Abruzzi  
Dept. of Economics of Engineering  
Stevens Inst. of Technology  
Hoboken, New Jersey 1

Prof. Stephen G. Allen  
School of Business Administration  
University of Minnesota  
Minneapolis, Minn. 1

Prof. Robert Bechhafer  
Dept. of Industrial Engineering  
Columbia University  
New York 3, N. Y. 1

Prof. Maurice H. Belz  
University of Melbourne  
Carlton N. 3  
Victoria, Australia 1

Prof. J. N. Berrettoni  
Western Reserve University  
Cleveland, Ohio 1

Mr. P. M. Blunk  
Quality Evaluation Laboratory  
U. S. Naval Magazine  
Port Chicago, California 1

Mr. Milton N. Bradley 632 Van Cortlandt Park Ave. Yonkers 5, N. Y.	1	Mr. Bernard P. Goldsmith Quality Control Engineer Raytheon Mfg. Co. 55 Chapel St. Newton 58, Mass.	1
Prof. Russell Bradt Dept. of Mathematics University of Kansas Lawrence, Kansas	1	Prof. Eugene L. Grant Civil Engineering Dept. Stanford University Stanford, California	1
Prof. Irving W. Burr Dept. of Mathematics Purdue University Lafayette, Indiana	1	Mr. Brent C. Jacob, Jr. Supervisor of Quality Inspection Chrysler Corp. Detroit 31, Michigan	1
Prof. Edward P. Coleman Engineering Dept. University of California Los Angeles 24, California	1	Mr. Calvin J. Kirchen Statistical Quality Control Analyst AF Plant Representative Central Air Procurement Division Kaiser Mfg. Corp. Willow Run, Michigan	1
Dr. Louis Court Division 17 National Bureau of Standards Washington 25, D. C.	1	Prof. Sebastian Littauer Dept. of Industrial Engineering Columbia University New York, N. Y.	1
Mrs. J. Henley Crosland Director of Libraries Georgia Inst. of Technology Atlanta, Ga.	1	Dr. William G. Madow Dept. of Mathematics University of Illinois Urbana, Illinois	1
Mr. H. F. Dodge Bell Telephone Labs, Inc. 463 West Street New York, N. Y.	1	Dean Paul E. Mohn School of Engineering The University of Buffalo Buffalo, N. Y.	1
Prof. Acheson J. Duncan School of Business The Johns Hopkins University Baltimore 18, Md.	1	Mr. L. E. Morris Q. E. Laboratory U. S. M. A. D. Bangor, Washington	1
Dr. Benjamin Epstein Dept. of Mathematics Wayne University Detroit, Michigan	1	Prof. E. G. Olds Dept. of Mathematics San Jose State College San Jose 14, California	1
Dr. George E. Forsythe National Bureau of Standards Inst. for Numerical Analysis University of California 405 Hilgard Ave. Los Angeles 24, California	1	Mr. John J. Riordan Chief, Quality Analysis Office Wright-Patterson Air Force Base Dayton, Ohio	1
Mr. S. Gaspar U. S. N. O. T. S. Pasadena Annex 125 S. Grand Ave. Pasadena, California	1	Mr. Harry G. Romig Quality Manager Hughes Aircraft Co. Culver City, California	1

Prof. Norman Rudy  
Statistics Dept.  
Sacramento State College  
Sacramento, California 1

Prof. Henry Scheffe  
Statistical Laboratory  
University of California  
Berkeley, California 1

Mr. R. H. Shaw  
U. S. Naval Ordnance Plant  
Indianapolis, Indiana 1

Mr. Walter Shewhart  
Bell Telephone Labs., Inc.  
Murray Hill, New Jersey 1

Prof. Herbert Solomon  
Teachers College  
Columbia University  
New York 27, N. Y. 1

Mr. M. D. Springer  
U. S. Naval Ordnance Plant  
Indianapolis, Indiana 1

Mr. Arthur Stein  
Ordnance Ammunition Center  
Joliet, Illinois 1

Miss Elizabeth Vaughan  
2325 7th St.  
Bremmerton, Washington 1

Prof. W. Allen Wallis  
Committee on Statistics  
University of Chicago  
Chicago 37, Illinois 1

Mr. Joseph Weinstein  
Evans Signal Laboratory  
Belmar, New Jersey 1

Prof. M. A. Woodbury  
Statistics Dept.  
Wharton School  
University of Pennsylvania  
Philadelphia 4, Pa. 1

Additional copies for project  
leader and assistants, office  
file, and reserve for future  
requirements 70

# Armed Services Technical Information Agency

Because of our limited supply, you are requested to return this copy WHEN IT HAS SERVED YOUR PURPOSE so that it may be made available to other requesters. Your cooperation will be appreciated.

# AD

# 40427

NOTICE: WHEN GOVERNMENT OR OTHER DRAWINGS, SPECIFICATIONS OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE U. S. GOVERNMENT THEREBY INCURS NO RESPONSIBILITY, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

Reproduced by  
**DOCUMENT SERVICE CENTER**  
KNOTT BUILDING, DAYTON, 2, OHIO

# UNCLASSIFIED